



**BRONMETAL**

**Bronce Br**

Producto formato:

Barra extruída / calibrada

Características técnicas:

Barras de bronce redondas extruidas y calibradas



## EQUIVALENCIAS

EN SIMBÓLICA	EN NUMÉRICA	UNE NUMÉRICA	UNE SIMBÓLICA	DIN	ISO	ASTM	BS
CuZn10	CW501L	C 6110	CuZn10	2.0230	CuZn10	C22000	CZ 101
CuZn15	CW502L	C 6115	CuZn15	2.0240	CuZn15	C23000	CZ 102
CuZn30	CW505L	C 6130	CuZn30	2.0265	CuZn30	C26000	CZ 106
CuZn33	CW506L	C 6133	CuZn33	2.0280	CuZn33	C26800	CZ 107
CuZn36	CW507L	C 6135	CuZn36	2.0335	CuZn36	C27000	-
CuZn37	CW508L	C 6137	CuZn37	2.0321	CuZn37	C27200	CZ 108
CuZn40	CW509L	C 6140	CuZn40	2.0360	CuZn40	C28000	CZ 109
CuZn37Mn3Al2PbSi	CW713R	C 6810		2.0550	CuZn40Al2	C67410	CZ 114

EN		DIN		ASTM	BS	JIS	SN
SIMBOLICA	NUMERICA	SIMBOLICA	NUMERICA				
CuSn5	CW451K	-	-	C51000	PB102	C5102	CuSn5
CuSn4	CW450K	CuSn4	2.1016	C51100	PB101	C5111	-
CuSn6	CW452K	CuSn6	2.1020	C51900	PB103	C5102	CuSn6
CuSn8	CW453K	CuSn8	2.1030	C52100	PB104	C5212 C5210	-
CuSn5Pb1	CW458K	-	.	C53400	-	C5341	CuSn5Pb1
CuSn4Pb4Zn4	CW456K	-	.	C54400	-	C5441	CuSn4Pb4Zn4
CuAl9Ni3Fe2	CW304G	-	-	-	-	-	-
CuAl10Fe1	CW305G	SG-CuAl10Fe	2.0937	C61800	CA103	-	CuAl10Fe1
CuAl10Fe3Mn2	CW306G	CuAl10Fe3Mn2	2.0936	-	-	-	CuAl10Fe3Mn2
CuAl10Ni5Fe4	CW307G	CuAl10Ni5Fe4	2.0966	C63000	-	-	CuAl10Ni5Fe4
CuAl11Fe6Ni6	CW308G	CuAl11Fe6Ni6	2.0978	-	-	-	-