



BRONMETAL

Copper Cu

Producto formato:

Profiles

Características técnicas:

Copper profiles for electrical applications



B Y H DIMENSIONAL TOLERANCES AND RELATIONSHIP

Nominal dimensions <i>b</i> and <i>h</i>		Tolerances for the dimensions <i>b</i> and <i>h</i> within a circumscribed circle		
Greater than	Until included	to 50 inclusive	Greater than 50 to 120 inclusive	Greater than 120 to 180 inclusive
-	10	± 0,11	± 0,18	± 0,29
10	18	± 0,14	± 0,22	± 0,35
18	30	± 0,17	± 0,26	± 0,42
30	50	± 0,20	± 0,31	± 0,50
50	80	-	± 0,37	± 0,60
80	120	-	± 0,44	± 0,70
120	180	-	-	± 0,80

THICKNESS TOLERANCES

Nominal thickness		Tolerances for the dimensions <i>b</i> and <i>h</i> within a circumscribed circle	
Greater than	Until included	to 50 inclusive	Greater than 50 to 180 inclusive
-	3	± 0,13	± 0,20
3	6	± 0,15	± 0,24
6	10	± 0,18	± 0,29
10	18	± 0,22	± 0,35
18	30	± 0,26	± 0,42
30	50	-	± 0,50