



BRONMETAL

Copper Cu

Product format: Flat bar

Technical characteristics: Flat copper bar /
rectangular rods for electrical application.

TOLERANCES

Nominal width ^a		Nominal thickness tolerance for the thickness range						
Greater than	Up to and including	Width tolerance	From 0,5 to 3 included	Greater than 6 to 10 included	Greater than 10 to 18 included	Greater than 18 to 30 included	mayor que 18 hasta 30 incluido	Greater than 30 to 40 included
1 ^b	10	±0,08	±0,05	±0,06	±0,08	-	-	-
10	18	±0,10	±0,05	±0,06	±0,08	±0,10	-	-
18	30	±0,15	±0,05	±0,07	±0,09	±0,10	±0,15	-
30	50	±0,20	±0,06	±0,09	±0,10	±0,12	±0,15	±0,20
50	80	±0,25	±0,09	±0,10	±0,12	±0,15	±0,18	±0,25
80	120	±0,30	-	±0,12	±0,15	±0,18	±0,23	±0,30
120	160	±0,40	-	-	±0,18	±0,20	±0,20	±0,35
160	200	±0,50	-	-	±0,20	±0,25	±0,30	±0,40

NOTE – Values in millimeters

^a When the relationship between the nominal width and the nominal thickness is greater than 20:1, the tolerances must be agreed between the client and supplier.

^b Including the value 1