



BRONMETAL

Copper Alloy CuA

Product format:

Plate

Technical characteristics:

Flats rectangular copper alloy

TOLERANCES

Nominal width			Nominal thickness tolerance for the thickness range					
Greater than	Until included	Width tolerance	From 3 to 6 inclusive	Greater than 6 to 10 inclusive	Greater than 10 to 18 inclusive	Greater than 18 to 30 inclusive	Greater than 30 to 50 inclusive	Greater than 50 to 60 inclusive
Tolerance class A								
6 ^a	18	± 0,27	± 0,18	± 0,22	± 0,27	-	-	-
18	30	± 0,33	± 0,18	± 0,22	± 0,27	± 0,33	-	-
30	50	± 0,62	± 0,22	± 0,27	± 0,33	± 0,45	± 0,62	-
50	80	± 1,20	± 0,27	± 0,33	± 0,45	± 0,52	± 0,74	± 1,00
80	120	± 2,20	± 0,33	± 0,45	± 0,52	± 0,74	± 1,00	± 1,20
Tolerance class B								
6 ^a	18	± 0,15	± 0,10	± 0,12	± 0,15	-	-	-
18	30	± 0,22	± 0,10	± 0,12	± 0,15	± 0,22	-	-
30	50	± 0,30	± 0,13	± 0,15	± 0,18	± 0,22	± 0,30	-
50	80	± 0,37	± 0,16	± 0,18	± 0,22	± 0,30	± 0,37	-
80	120	± 0,45	± 0,18	± 0,22	± 0,27	± 0,35	± 0,45	-
^a Including 6.								