

Tolerances

Nominal Width		Width Tolerance	Tolerance of nominal thickness for the range of thicknesses						To ler an ce cla ss A
Greater than	Up to and including		from 3 up to and inc. 6	greater than 6, up to and inc. 10	greater than 10, up to and inc. 18	greater than 18, up to and inc. 30	greater than 30, up to and inc. 50	greater than 50, up to and inc. 60	
6 ^a	18	± 0,27	± 0,18	± 0,22	± 0,27	—	—	—	
18	30	± 0,33	± 0,18	± 0,22	± 0,27	± 0,33	—	—	
30	50	± 0,62	± 0,22	± 0,27	± 0,33	± 0,45	± 0,62	—	
50	80	± 1,20	± 0,27	± 0,33	± 0,45	± 0,52	± 0,74	± 1,00	
80	120	± 2,20	± 0,33	± 0,45	± 0,52	± 0,74	± 1,00	± 1,20	
Tolerance class B									
6 ^a	18	± 0,15	± 0,10	± 0,12	± 0,15	—	—	—	
18	30	± 0,22	± 0,10	± 0,12	± 0,15	± 0,22	—	—	
30	50	± 0,30	± 0,13	± 0,15	± 0,18	± 0,22	± 0,30	—	
50	80	± 0,37	± 0,16	± 0,18	± 0,22	± 0,30	± 0,37	—	
80	120	± 0,45	± 0,18	± 0,22	± 0,27	± 0,35	± 0,45	—	

^a including 6.