

# Tolerances

Nominal Width <sup>a</sup>		Width Tolerance	Tolerance of nominal thickness for the range of thicknesses					
Greater than	Up to and including		From 0.5 up to and including 3	Greater than 3, up to and inc. 6	Greater than 6, up to and inc. 10	Greater than 10, up to and inc. 18	Greater than 18, up to and inc. 30	Greater than 30, up to and inc. 40
1 <sup>b</sup>	10	± 0,08	± 0,05	± 0,06	± 0,08	—	—	—
10	18	± 0,10	± 0,05	± 0,06	± 0,08	± 0,10	—	—
18	30	± 0,15	± 0,05	± 0,07	± 0,09	± 0,10	± 0,15	—
30	50	± 0,20	± 0,06	± 0,09	± 0,10	± 0,12	± 0,15	± 0,20
50	80	± 0,25	± 0,09	± 0,10	± 0,12	± 0,15	± 0,18	± 0,25
80	120	± 0,30	—	± 0,12	± 0,15	± 0,18	± 0,23	± 0,30
120	160	± 0,40	—	—	± 0,18	± 0,20	± 0,20	± 0,35
160	200	± 0,50	—	—	± 0,20	± 0,25	± 0,30	± 0,40

NOTE – Values in millimetres

<sup>a</sup> When the relation between nominal width and nominal thickness is greater than 20:1, tolerances must be agreed on between client and supplier.
<sup>b</sup> Includes the value 1.